



CONCRETE CORE DRILLS

HUSQVARNA DM 400

Art.no: 967 91 03 01

DM 400 is a powerful and sturdy electric core drill for medium to heavy core drilling where reliability and high productivity is needed. Recommended diameter 55-350 mm. With aluminium motor housing to withstand tough handling and a carrying handle for ergonomic usage and additional impact protection of the drill motor. Equipped with Embedded Connectivity, an enhanced version of Husqvarna Fleet Services™ for data analytics and insights into the health of the machine. Suitable for water evacuation, ventilation, angle drilling, stitch drilling and when you need to cut close to corners.

FEATURES



Sturdy and durable

Equipped with an aluminium housing and the protective carrying handle ensures rough handling.



Ergonomic

Equipped with a carrying handle for easy transport and handling.



Optimised RPM's

Enables high drilling performance.



Embedded Connectivity

An enhanced version of Husqvarna Fleet Services™. Enables data analytics and insights into the health of the machine.

TECHNICAL DATA HUSQVARNA DM 400

Art.no: 967 91 03 01

HUSQVARNA DM 400

MOTOR

Rated input power	3.2 kW
Frequency	50-60 Hz
Voltage	220-240 V
Phases	1 ph
Power source	Corded

EQUIPMENT

Drill bit diameter with stand, max	350 mm
Recommended drill bit diameter, min	55 mm
Coolant	Wet

TRANSMISSION

Number of gearbox speeds	3
Spindle speed unloaded gear 1	420 rpm
Spindle speed unloaded gear 2	820 rpm
Spindle speed unloaded gear 3	1,250 rpm

PRODUCT DATA

Water connector	G 1 / 4"
Water pressure, max	3 bar
Spindle thread, outer	1 1/4" 7 UNC

DIMENSIONS

Product size length	546 mm
Product size width	138 mm
Product size height	185 mm
Weight (complete product w/o side packed articles)	14 kg
Packaging length	625 mm
Packaging width	255 mm
Packaging height	300 mm
Article gross weight	16,600 g

SOUND AND NOISE

Sound power level, guaranteed (LWA)	112 dB(A)
Sound power level, measured	110 dB(A)
Sound pressure level at operators ear (LpA)	92 dB(A)



View all product details on:

<https://www.husqvarnaconstruction.com/asia/concrete-core-drills/dm400/>



**DIAMOND CORE DRILL BITS
ELITE-DRILL™ D1610**

Diameter mm:
52/-/350mm
Drill connection:
1 1/4" / CR128
Core length mm:
500 mm
Coolant:
Wet



**DIAMOND CORE DRILL BITS
ELITE-DRILL™ D1620**

Diameter mm:
52/-/350mm
Drill connection:
1 1/4" / CR128
Core length mm:
500 mm
Coolant:
Wet



**DIAMOND CORE DRILL BITS
ELITE-DRILL™ D1640**

Diameter mm:
16/-/350mm
Drill connection:
1 1/4" / CR128
Core length mm:
500 mm
Coolant:
Wet



**DIAMOND CORE DRILL BITS
VARI-DRILL™ D20**

Diameter mm:
16/-/300mm
Drill connection:
1 1/4"
Core length mm:
500 mm
Coolant:
Wet



**DIAMOND CORE DRILL BITS
VARI-DRILL™ D65**

Diameter mm:
52/-/300mm
Drill connection:
1 1/4"
Core length mm:
500 mm
Coolant:
Wet



**DIAMOND CORE DRILL BITS
TACTI-DRILL™ D20**

Diameter mm:
52/-/300mm
Drill connection:
1 1/4"
Core length mm:
500 mm
Coolant:
Wet



**CORE DRILL STANDS
DS 500**

Weight (complete product w/o side packed articles):
17.6 kg
Drill bit diameter, max:
500 mm
Travel length, max:
706 mm
Column's angling:
0-90°



**SLURRY AND WET VACUUMS
W/70 P**

Power source:
Corded
Phases:
1 ph
Air requirement:
200 m³/h
Rated input power:
1.85 kW



**SLURRY RINGS/COLLECTORS
SLURRY RINGS WSR**

Accessory for:
Dust collectors, Drill motors



**CORE DRILL STANDS
DS 50 GYRO**

Weight (complete product w/o side packed articles):
56.5 kg
Drill bit diameter, max:
350 mm
Travel length, max:
670 mm
Column's angling:
+/-90°



**SLURRY RINGS/COLLECTORS
SLURRY COLLECTOR
V-SHAPED**

Accessory for:
Drill stands, Drill motors, Drill motors with stand



**BATTERY POWERED PRODUCTS
WT 15I**

Battery eco system:
BLi-X
Water pressure, max:
0.9 bar
Weight (complete product w/o side packed articles):
3.6 kg
Hose length:
3 m



**SLURRY RINGS/COLLECTORS
SLURRY COLLECTOR
U-SHAPED**

Accessory for:
Drill stands, Drill motors, Drill motors with stand



[husqvarnaconstruction.com](https://www.husqvarnaconstruction.com)