



CONCRETE CORE DRILLS

HUSQVARNA DMS 240

Art.no: 965 17 36 03

DMS 240 is an electric drill motor and stand system for a huge variety of core drilling applications. It is the most powerful system in our drill motor stand range. An ideal system for medium core drilling in walls, floors and roofs up to 250 mm diameter. The stand is easy to tilt, the back support provides reliable and stable angle drilling, saving you setup time and body stress. This system can be used for drilling ventilation and plumbing channels, waste evacuation pipes as well as barrier and road signs.

FEATURES



Optimum cranking speed

Carriage with single and double gearing for efficient drilling.



User-friendly base plate

Lightweight base plate made of aluminium with integrated vacuum base, means fast setup with no damages to the surroundings.



Overload protection

Increases productivity and extends service life.



Easy transportation

The stand is equipped with transport wheels.

TECHNICAL DATA HUSQVARNA DMS 240

Art.no: 965 17 36 03

HUSQVARNA DMS 240

MOTOR

Rated input power	2.4 kW
Frequency	50 Hz
Voltage	220-240 V
Phases	1 ph
Power source	Corded

EQUIPMENT

Recommended drill bit diameter, min	0 mm
Drill bit diameter, max	250 mm
Coolant	Wet

TRANSMISSION

Number of gearbox speeds	2
--------------------------	---

PRODUCT DATA

Water connector	G 1 / 4"
Water pressure, max	8 bar
Spindle thread, inner	G 1/2"
Spindle thread, outer	1 1/4" 7 UNC
Column's angling	0-60°
Column installation	Tilttable

DIMENSIONS

Rated current	10 A
Travel length, max	685 mm
Product size length	545 mm
Product size width	266 mm
Product size height	1,052 mm
Weight (complete product w/o side packed articles)	27.5 kg
Packaging length	1,150 mm
Packaging width	530 mm
Packaging height	330 mm
Article gross weight	34,000 g

SOUND AND NOISE

Sound power level, guaranteed (LWA)	107 dB(A)
Sound power level, measured	106 dB(A)
Sound pressure level at operators ear (LpA)	90 dB(A)



View all product details on:

<https://www.husqvarnaconstruction.com/asia/concrete-core-drills/dms240/>

RELATED CONSUMABLES



DIAMOND CORE DRILL BITS VARI-DRILL™ D20

Diameter mm:
16/-/300mm
Drill connection:
1 1/4"
Core length mm:
500 mm
Coolant:
Wet



DIAMOND CORE DRILL BITS VARI-DRILL™ D65

Diameter mm:
52/-/300mm
Drill connection:
1 1/4"
Core length mm:
500 mm
Coolant:
Wet



DIAMOND CORE DRILL BITS TACTI-DRILL™ D20

Diameter mm:
52/-/300mm
Drill connection:
1 1/4"
Core length mm:
500 mm
Coolant:
Wet

RELATED EQUIPMENT & ACCESSORIES



WATER TANKS WT 15I

Water pressure, max:
0.9 bar
Water Tank Capacity:
15 l
Weight (complete product w/o side packed articles):
3.6 kg
Hose length:
3 m



WATER TANKS WT 10 MP

Water Tank Capacity:
10 l
Weight (complete product w/o side packed articles):
2.35 kg



SLURRY AND WET VACUUMS W/250 P

Power source:
Corded
Phases:
1 ph
Air requirement:
160 m³/h
Rated input power:
1.55 kW



SLURRY RINGS/COLLECTORS SLURRY RINGS WSR

Accessory for:
Dust collectors, Drill motors



[husqvarnaconstruction.com](https://www.husqvarnaconstruction.com)